



Declaration of Conformity

| For the following equipmer | nt: | |
|--|--|--|
| Product Name: Switching I | Power Supplies | |
| Model Designation: DR-10 | 0-X (X=12,15,24) | |
| is herewith confirmed to c were applied : | comply with the requirements set out | t in the Council Directive, the following standards |
| RoHS Directive (2011 Low Voltage Directive (| | |
| EN60950-1:2006+A11+A1 | +A12+A2 TUV certificate No: R50 | 0113593 |
| Electromagnetic Comp EMI (Electro-Magnetic In Conducted emission / Rad | | : Class B |
| Harmonic current | EN61000-3-2:2006+A1:2009+A2:20 | 2009 |
| Voltage flicker | EN61000-3-3: 2008 | |
| EMS (Electro-Magnetic S | usceptibility) | |
| EN55024:2010 | | |
| ESD air | EN61000-4-2:2009 | Level 3 8KV |
| ESD contact | EN61000-4-2:2009 | Level 2 4KV |
| RF field susceptibility | EN61000-4-3:2006+A1:2008+A2:20 | 010 Level 3 10V/m |
| EFT bursts | EN61000-4-4:2012 | Level3 2KV/5KHz |
| Surge susceptibility | EN61000-4-5:2006 | Level 3 2KV/Line-Line |
| Surge susceptibility | EN61000-4-5:2006 | Level 4 4KV/Line-FG |
| Conducted susceptibility | EN61000-4-6:2009 | Level 3 10V |
| Magnetic field immunity | EN61000-4-8:2010 | Level 4 30A/m |
| Voltage dip, interruption | EN61000-4-11:2004 >95% dip 0.5 perio | ods 30% dip 25 periods >95% interruptions 250 periods |
| performance will be affected to complete system again. | | ated in combination with final equipment. Since EMC ent manufacturers must re-qualify EMC Directive on the (Technical Documentation File). |
| This Declaration is effective from | om serial number HB6xxxxxxx | |
| Person responsible for ma | rking this declaration: | |
| MEAN WELL Enterprises (| Co., Ltd. | |
| (Manufacturer Name) | | |
| No.28, Wuquan 3rd Rd., W (Manufacturer Address) | /ugu Dist., New Taipei City 248, Taiwa | an A.A.A. |
| Johnny Huang/Manager, Certific (Name / Position) | 7 000 | I Cheng/Director, Sales Dept. : (Signature) |
| Taiwan (Place) | Apr. 20th, 2016 (Date) | _ |