

Data sheet:

## Plug-in Power Supply, 24V / 750mA DC with US plug



Article no.: 11027

**EUR 29.00**

\*Net price for commercial users

[Add to cart](#) [Sample order](#) [Request a quote](#) [Contact](#) [Manual](#) [More AC adapters](#)

Versatile plug-in power supply

24V power supply with 85% efficiency and with low standby losses &lt; 0.1W (per DoE Level VI)

### Properties

#### General Data

- 24V AC adapter
- High efficiency: min. 85%
- Low standby losses < 0.1W (per DoE Level VI)
- Limited Power Source (LPS)
- Flexible in application:
  - Primary-side interchangeable adapter system
  - Generous 100...240V input range
  - CE Marking as well as UL / cUL and CCC approval
- Compact form factor: 74 x 43.5 x 34 mm

#### Standards & more

- **Conforms to standards in the office and small business environment**
  - Noise emission and noise immunity for residential and commercial areas
- **5 year guarantee**

Wish for something!  
[Your suggestions for improvement and additions](#)

---

### Technical data

Input voltage: 100...240VAC  
Frequency: 50...60Hz  
Input current: max. 0.6A

Output voltage: 24V DC  
Tolerance: ±5%  
Ripple: max. 150mV  
Output power: max. 18W  
Rated current: 0.75A, short-circuit protected  
Minimum load: none

Efficiency: min. 85%  
No-load losses: <0.1W per DoE Level VI  
LPS: Yes

Dielectric strength: In-Out: 3KV AC  
Leakage current: < 0.25mA

Mains connection: US adapter  
(multi-adapter system)  
Secondary connection: 2-pole special connector for screw terminal  
Cable type: Twin leads with ferrite core  
Cable length: 1.8 meters

Operating temperature: 0..40°C  
Storage temperature: -10..70°C  
Relative humidity: 20...80% rH (non-condensing)  
MTBF: >200,000 hours (per MIL-HDBK-217F at 25° C)

Dimensions: 74 x 43.5 x 34 mm (L x W x H)  
Weight: 140 g



Approvals: CE, GS, UL, c-UL, CCC  
Safety standard: EN 60950-1  
EMC - Emission: EN 55032 B  
EN 61000-3-2, EN 61000-3-3  
EMV - Noise immunity: EN 55024  
EN 61000-4-2, EN 61000-4-3  
EN 61000-4-4, EN 61000-4-5  
EN 61000-4-6, EN 61000-4-8  
EN 61000-4-11

Manufacturer: GlobTec Inc.  
GlobTek Deutschland GmbH  
Hafenweg 26a  
48155 Münster

Power supply type: GT-46180-1824

---

#### Article list

|  |       | *Net unit price for commercial users   |
|--|-------|--|
| Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug | 11026 | 34.00€  |
| Plug-in Power Supply, 24V / 750mA DC with Euro plug            | 11025 | 29.00€  |
| Plug-in Power Supply, 24V / 750mA DC with US plug              | 11027 | 29.00€  |

\* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis  
GmbH  
Porschestra. 12  
42279 Wuppertal  
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)  
Fax: +49 202/2680-265  
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)