

Data sheet:

## Power supply for DIN rail, 24V/2.5A DC



Article no.: 11076

This power supply has been replaced by the successor model 11079.



### 60W power supply

Versatile DIN rail power supply with wide-range input 100..240V

### Properties

- High efficiency: typ. 84%
- Large operating temperature range: -20..+60 degrees Celsius
- Compact DIN rail housing: 93 x 78 x 56
- Standards-conformal for both office and industrial environments:
  - Increased noise immunity for industrial areas
  - Stricter noise emission for residential and commercial areas

### Background information

W&T Interfaces or Com-Servers are frequently used with a 24V power supply in large numbers at a central location. In such cases a common supply for the interfaces makes the application significantly clearer than would be the case when powering the devices with individual dedicated power supplies.

If there is no high-capacity 24V power supply in the installation, this task can be elegantly and cost-effectively solved using the #11076 60W DIN rail mounted power supply, with which multiple Interfaces or Com-Servers can be powered centrally.

The power supply can of course also be used where in addition to the 24V supply for the W&T Interface you also need power for the rest of the installation. In this case you simply need to ensure that the power consumed does not exceed the rated power of the DIN rail power supply.

Thanks to the generous operating temperature range, the DIN rail mount power supply is also ideal for applications where the standard plug-in power supply provided with the Interfaces cannot be used due to the expected high ambient temperatures.

### Technical data

Output power:	max. 60W
Efficiency:	typ. 84%
Input voltage:	100..240VAC
Frequency:	47..63 Hz
Input current:	0.8A at 230V AC
Inrush:	max. 36A at 230V AC
Leakage current:	<1mA at 230V AC
Output voltage:	24V DC (adjustable 21.6..26.4V)
Tolerance:	+/-1%
Ripple:	max. 150mV
Rated current:	2.5A
Minimum load:	none
Overcurrent limiter:	at 105%...160% of the nominal current
Short circuit protected:	Yes
Overvoltage protection:	Shutdown at 115%..135% of nominal voltage Reset using POWER ON

Start time: 100ms at nominal load and 230V AC  
Rise time: 30ms at nominal load and 230V AC  
Voltage bridging: 100ms at nominal load and 230V AC

Cooling: Convection cooling  
Dielectric strength: In-Out: 3KV AC  
Isolation resistance: In-Out: 100 Mohm at 500VDC

Operating temperature: -20..60°C, power derating  
over 45..60°C: 2.6%/°C  
Storage temperature: -40..85°C  
Relative humidity: Operating: 20..90% relative humidity  
Storage: 10..95% relative humidity  
(non-condensing)

Connections: 2-pin input, 4-pin output  
with screw terminals  
MTBF: >216,200 hours (per MIL-HDBK-217F at 25° C)

Weight: 300 g  
Dimensions: 78 x 93 x 56 mm

Approvals: UL, c-UL, TÜV, CB, CE  
Safety: Meets  
UL 60950-1 / EN60950-1

EMC: Meets  
EN 55022 B  
EN 61000-3-2, EN 61000-3-3  
EN 61000-4-2, EN 61000-4-3  
EN 61000-4-4, EN 61000-4-5  
EN 61000-4-6, EN 61000-4-8  
EN 61000-4-11, ENV 50204  
EN 61204-3, EN 61000-6-2



[We are available to you in person:](#)

Wiesemann & Theis  
GmbH  
Porschestra. 12  
42279 Wuppertal  
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5  
p.m.)  
Fax: +49 202/2680-265  
[info@wut.de](mailto:info@wut.de)

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)