

Data sheet:

CompactPCI card 2x 20 mA



Article no.: 13421

Unfortunately, this article is no longer available.

Application:

For connecting any 20mA devices to a CompactPCI system

Properties

General information

- Upgrading of CompactPCI systems with 20 mA interfaces
- 1kV electrical isolation to the PC and between the ports
- connector-compatible to all W&T PC card ranges
- for 5 V cPCI slots
- PCI UART 16950 with 128 byte FIFO
- Software-compatible to W&T standard PCI cards
- Plug-and-play: automatic configuration of base address and interrupt
- Including drivers for:
- Includes drivers for Windows 95/98, NT4.0, 2000, XP and Vista
- Conforms to standards both in office and industrial environments:
 - Increased noise immunity for industrial areas
 - Stricter noise emission for residential and commercial areas

Background information:

Since the mid-1990s, the PCI bus has developed to become the standard bus of state-of-the-art PCs. With the development of the CompactPCI standard which combines the electrical features of the PCI bus with the mechanics of the long-standing and well-proven 19" world, this tried and tested bus system can also be deployed in the industrial environment.

W&T converted all serial standard PCI cards to the CompactPCI format in such a way that no differences in using the cards are noticeable by users who switch from one PC world to the other. Independently of the relevant PC bus being used (ISA, PCI or CompactPCI), all W&T PC card ranges have an identical design with a subdivision into bus-specific elements and modular interface electronics. In that way, it is ensured for all bus systems that the peripherals can always be connected with the same cables and without exotic adapters or adjustments.

The realization of the cards with discrete interface modules also enables various different interface models (RS-232, RS-422, RS-485 or 20 mA) to be realized on a single board. This feature guarantees the optimum utilization of the in most cases small number of available slots in CompactPCI systems.

Technical data

Number of ports:	2 galvanically isolated 20mA ports
Operating modes:	active or passive mode
UART:	16950 with 128-byte FIFO
Base addresses:	automatic configuration
Interrupts:	automatic configuration
Baud rate:	50..57,600 baud
Data format:	any format
Signals:	RxD+, RxD-, TxD+, TxD-
Serial connections:	9-pin SUB-D connector

Galvanic isolation: Isolation voltage min. 1 KV DC
between PC and serial ports
Power supply: +5V 0.2A, +12V 0.1A
Ambient temperature: Storage: -40..+70°C, Operation: 0..+70°C
Permissible relative humidity: 0..95% RH (non-condensing)
Dimensions: 160 x 100 mm (3HU)
Weight: approx. 170 g
Scope of delivery: CompactPCI card 2x 20 mA
Driver CD



[We are available to you in person:](#)

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)