

Data sheet:

ISA card 2x RS232 without galvanic isolation



Article no.: 13801

EUR 188.00

*Net price for commercial users

Add to cart

Sample order

Request a quote

Contact

Manual

Two additional RS232 ports for older PCs

The 13801 PC Card adds two serial RS232 ports to your older PC and needs no additional driver software.

Properties

Interfaces:

- 2x RS232 interface
- 1x 16-bit ISA bus

Management and connectivity:

- Manual configuration by means of DIL switch
- Flexible configuration
 - Standard base addresses COM1-COM4
 - custom base addresses possible
 - Interrupts IRQ3-IRQ7, IRQ9-IRQ12
- UART 16550 with FIFO
- Software compatible with standard RS232 cards
- No additional driver software required

Standards & more

- Conforms to standards both in office and industrial environments:
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- 5 year guarantee

Wish for something!
Your suggestions for improvement and additions

Technical data

Connections and displays:

System bus:	16-bit ISA bus / 8.33 MHz
Serial port:	2x RS232 interface 9-pin SUB-D adapter
Operating mode:	RS232
Maximum baud rate:	115.200 kbaud
Data format:	any format
Signals:	RxD,TxD,RTS,CTS,DSR,DCD,DTR,RI
Handshake:	No, RTS/CTS, Xon/Xoff
UART:	16550 with FIFO
Base addresses:	03F8H, 02F8H, 03E8H, 02E8H
Interrupts:	IRQ 3..7, IRQ 9..12
Galvanic isolation:	none
Supply voltage:	5V DC
Current consumption:	typ. 200mA

Housing and other data:

Dimensions: 145 x 120 mm (W x H)
Enclosure rating: IP00
Weight: approx. 90g
Ambient temperature: Storage: -40..+70°C
Operating: 0..+70°C
Permissible relative humidity: 5..95% RH, non-condensing
Scope of delivery: ISA card 2x RS232
Manual

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wieseemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wieseemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)