

Data sheet:

Digital-I/O Extender Set 8*In / 8*Out Multimode ST



Article no.: 17634

EUR 888.00

*Net price for
commercial users

Reliably send contact signals over long distances

The Digital I/O Extender Set 8x8 sends up to 16 digital I/O signals over multi-mode fiber optic cable. The set consists of two Digital-I/O <> glass fiber optics and supports eight I/O channels in each direction.

Properties

Interfaces:

- **8 x digital output**
 - FET, short-circuit protected, 8..30V / 0.5A
- **8 x digital input**
 - Polarity reversal protected
- **1 x multi-mode fiber optic cable**
 - ST connector

Management and connectivity:

- **Noise-immune transmission of 16 I/O signals over a distance of up to 3800 meters, e.g.:**
 - in extremely noisy industrial environments
 - in areas subject to lightning strikes
 - between two distant buildings
 - in the mountains
 -
- **Safety-optimized solution**
 - No need for programmable components: No firmware risk
 - Integrated monitoring of the fiber optic connection: Status output on each converter
 - configurable output response when glass-fiber cable is interrupted

Power supply:

- **External**
 - 8V-30V DC using plug-in screw terminal

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance per EN 61000-6-2
 - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3
- **5 year guarantee**

 Wish for something!
Your suggestions for improvement and additions

Worth knowing

Although digital I/O signals are essentially insensitive to external noise due to their low bandwidth and the large voltage

swing, as serial data signals for example the application conditions do still in many cases require transmission procedures which are completely resistant to local noise effects.

Glass fiber optic cables used as the transmission medium meet these requirements in ideal fashion and also offer the advantage of galvanic isolation of up to virtually any value between the connected devices. In installations which are subjected to high risk of lightning strikes, for example in outdoor locations or between distant buildings, such a solution ensures that the connected components will survive even under adverse conditions.

The W&T Digital-I/O Extender Set 8x8 is fully implemented in hardware, so that there is no principle risk of malfunction caused by hidden firmware errors or by a system crash.

The functionality of the glass fiber optic connection is cyclically monitored and the status indicated by means of an LED and a switching output. Should the connection fail, the fallback state can be individually set for each digital output.

Technical data

Connections and displays:

I/O connection:	Plug-in screw terminal
Digital outputs:	8 x Digital Out 8V-30V, 500mA, short circuit protected, configurable response to failure of the optical connection
Digital inputs:	8 x Digital In, max. input voltage $\pm 30V$, protected against reverse connection within this range, Switching threshold $9V \pm 1V$, "On" current = 2.2mA
Glass fiber connection:	ST plug adapter
Supported signals:	16 digital signals (eight in each direction)
Signal propagation time:	Input to output: max. 20ms
Fiber optic medium:	Multi-mode fiber 50/125 μm , 62.5/125 μm
Transmitter type:	LED
Wavelength:	820nm
Optical budget:	50/125 μm : typically 9.6dB, min. 4.2dB 62.5/125 μm : typically 13.4dB, min. 8.0dB
Maximum distance:	50/125 μm : typically 3200m, min. 1400m @3dB/km 62.5/125 μm : typically 3800m, min. 2200m @3.5dB/km
Supply voltage:	8..30V DC
Current consumption:	typ. 20mA @12V DC
Supply connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Displays:	8x LED inputs 8x LED outputs 1x LED Link 1x LED Power

Housing and other data:

Housing:	Plastic housing for top hat rail installation 105 x 45 x 75mm (L x W x H)
Enclosure rating:	IP20
Weight:	approx. 400g
Ambient temperature:	Storage: -40..+70°C, Operation: 0..+70°C
Permissible relative humidity:	5..90% relative humidity (non-condensing)
MTBF:	326,086h @25°C per MIL-HDBK-217
Life expectancy:	> 25 years at 25°C ambient temperature
Scope of delivery:	2 Converters Digital-I/O <> Multi-Mode Glass Fiber If needed please order power supplies as separate accessories

Accessories

*Net unit price for commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug

11021 21.00€ 

Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug 11026 38.00€ 

Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee) 11080 33.00€ 

FO-Accessories

Patch cable ST/ST, 1 meter, 50/125um 81901 16.00€ 

Patch cable ST/ST, 2 meters, 50/125um 81902 21.00€ 

Patch cable ST/ST, 5 meters, 50/125um 81905 26.00€ 

Patch cable ST/ST, 10 meters, 50/125um 81910 37.00€ 

Patch cable ST/ST, 15 meters, 50/125um 81915 42.00€ 

Mechanical Accessories

Mounting bracket for wall mounting 58812 11.20€ 

19" DIN rail 58813 21.00€ 

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



www.WuT.de

We are available to you in person:

Wiesemann & Theis GmbH

Porschestraße 12

42279 Wuppertal

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)

Fax: +49 202/2680-265

info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)