

Data sheet:

RS232/RS422/RS485 interface module, 3.3V technology


for serial PC cards and Com-servers using 10/100BT



Article no.: 18833

EUR 55.00

*Net price for commercial users

Add to cart Sample order Request a quote Contact Manual 

Freely selectable serial interface

W&T interface modules equip devices having only a serial TTL interface with almost any desired standard interface type. In addition the modules allow you to adapt the interface types of many W&T devices over a wide range. The modification is done by simply replacing the standard interface modules with modules of the desired interface type.

Properties

Interfaces:


- **1 x serial standard interface**
 - 9-pin SUB-D connector
- **1 x TTL interface**
 - 12-pin male header with 2mm spacing

Management and connectivity:

- **Tiny plug-in interfaces**
- **Interface**
 - RS232/RS422/RS485 combi-module (switchable interface type)

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

 Wish for something!
Your suggestions for improvement and additions

Technical data

Connections and displays:

TTL plug adapter:	Terminal strip, 2mm spacing
Serial port:	9-pin SUB-D adapter
Operating modes:	RS232 RS422 RS485 2/4 wire with handshake control RS485 2/4 wire with automatic control
Switching time:	approx. 10µs for switching from data send to receive for RS485 automatic control (can be changed on request)
Transfer rate:	RS232: max. 1MBaud RS422/RS485: max. 10MBaud
Signals:	RS232: RxD, TxD, RTS, CTS, DSR, DCD, DTR, RI RS422: RxD, TxD, CTS, DTR RS485: RxD, TxD
Termination:	Connectable termination network
Power supply:	3.3V, 40mA (typ.)

Dimensions and other data

Dimensions: 45 x 32 x 14mm (L x W x H)
Enclosure rating: IP00
Weight: approx. 15g



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)