

Data sheet:

Centronics Portable Buffer 32KB



Article no.: 22031

Unfortunately, this article is no longer available.

Contact 

Transporting print data

Properties

General information

- Save print data and print it wherever you need it.
- Demo box for printers
- User-friendly
- Pocket size

Background information:

Sometimes, it is not possible to lay a cable between the computer and printers or other devices. However, the transfer of data on disks is often not practical (due to incompatibility or the lack of a floppy drive at the devices), or simply too cumbersome and risky (viruses). Printouts of logs are normally only required in the event of a disruption. Why should such data therefore be printed constantly? In these situations, portable buffers are the ideal solution. They are connected to the computer instead of a printer, and all print data is read into the buffer.

Technical data

Capacity:	32 KB, 128 KB, 512 KB
Transfer rate:	100 kcps
Power supply:	6V lithium battery, type BR2325
Idle current:	<1 uA
Input/output:	36-pin Centronics adapter, buffer Can be plugged directly to the printer
Housing:	Plastic housing, 75x61x20 mm
Weight:	180 g, incl. adapter cable
Scope of delivery:	1 x Centronics portable buffer 1 x adapter cable holder 36-pin Centronics socket/ 36-pin Centronics socket

We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)