Data sheet:

Centronics > RS232 interface

Article no.: 28000

EUR 228.00

*Net price for commercial users

Continue to use serial printers.

The Interface 28000 allows unidirectional connection of RS232 peripherals to computers which only have a parallel printer port.

Properties

Interfaces:

- **1 x RS232 output**
  - 25-pin SUB-D plug with DTE pin functions
- **1 x Centronics input**
  - 36-pin Centronics socket

Management and connectivity:

- **Continue to use serial printers.**
- **Suitable for a wide range of applications:**
  - Transfer rate up to 76,800 baud
  - Definable data format
  - Selectable hardware handshake or XON/XOFF protocol

Power supply:

- **External**
  - via supplied AC adapter (only with Euro plug)

Standards & more

- **Conforms to standards both in office and industrial environments:**
  - High noise resistance per EN 61000-6-2
  - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3
- **5 year guarantee**

Wish for something!
Your suggestions for improvement and additions

Technical data

Connections and displays:

Parallel port:	36-pin Centronics socket with 50cm connection cable on device
Serial port:	RS232 Interface 25-pin SUB-D plug in housing
Baud rate:	150 .. 76,800 baud
Data format:	7, 8 data bits, No, Even, Odd Parity

Handshake:	DTR or XON/XOFF handshake
Supply voltage:	5V DC
Current consumption:	approx. 60mA
Supply connection:	Jack plug, 2.5mm diameter
Displays:	1 LED Power

Housing and other data:

Housing:	Plastic housing, 124 x 74 x 21mm (L x W x H)
Enclosure rating:	IP20
Weight:	425g incl. power adapter
Ambient temperature:	Storage: 0..+70°C Operating: 0..+40°C
Permissible relative humidity:	5..95% RH, non-condensing
Scope of delivery:	Centronics > RS232 interface AC adapter for office use (only with Euro plug)

Accessories

*Net unit price for commercial users

Cable and Connector Accessories

PC Parallel Printer Cable, 2m	11822	9.90€

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.

W&T
www.WuT.de

We are available to you in person:

Wiesemann & Theis GmbH
Porschestr. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

Data Privacy