

Data sheet:

Interface USB <=> 20mA Industry, Bus Powered



Article no.: 34211

EUR 158.00*Net price for
commercial users

Add a 20mA interface to your PC system

The model 34211 interface expands your system with a 20mA interface for connecting active and passive 20mA devices through a USB cable.

Properties

Interfaces:

- 1 x USB socket, type B
- 1 x 20mA, 9-pin SUB-D plug
 - active or passive
- Galvanic isolation between the ports
 - Isolation voltage min. 1kV DC

Management and connectivity:

- USB 2.0 Full Speed Device (12 Mbit/s)
- Industry-compatible design on account of
 - noise immunity in accordance with EN 61000-6-2
 - Housing for top-hat-rail installation
- Active/passive mode for transmission and reception loop, individually adjustable
- Optional full- and half-duplex mode with echo suppression
- Addressable as virtual COM interface under
 - Windows 98 / Me / 2000
 - Windows XP / Vista / 7 / 8 / 8.1 / 10 (x86 and x64)
 - Windows Server 2003 / 2008 / 2008R2 / 2012 / 2012R2 (x86 and x64)
- Supports Mac OS X

Power supply:

- No additional power supply required
 - Voltage supply via the USB
 - Galvanically isolated power connection

Standards & more

- Conforms to standards both in office and industrial environments:
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- 5 year guarantee

♥ Wish for something!
Your suggestions for improvement and additions

Worth knowing

Overvoltage protection for serial interfaces

The permissible voltages allowed to have an effect on serial ports in case of an error are limited to rather low values according to the data sheet specifications for the interface components. Voltages which exceed these values even for a short time will inevitably result in damage to or even destruction of the integrated circuits.

To prevent such effects the USB-Interface 34211 includes integrated overvoltage protection which uses suppressor diodes to limit the maximum occurring voltages to harmless values in a variety of applications.

Technical data

Connections and displays:

USB port:	Type B female
20mA port:	9-pin SUB-D adapter
Operating modes:	active or passive mode Full- or half-duplex mode Selectable echo suppression in half-duplex mode
Baud rate:	300..19,200 baud
Data format:	Data bit: 7,8 Stop bit: 1,2 Parity: odd, even, no, mark, space
Signal lines:	RxD+/-, TxD+/-
Galvanic isolation:	Isolation voltage min. 1kV DC between USB and serial connection
USB-UART:	FTDI FT232R
Power supply:	5V DC over USB, optional supply from external 5V power supply
Current consumption:	max. 200mA
Displays:	1x LED Data 1x LED On Line


Housing and other data:

Housing:	Plastic housing for top hat rail installation 105 x 22 x 75mm (L x W x H)
Enclosure rating:	IP20
Enclosure rating:	IP20
Weight:	approx. 170g
Ambient temperature:	Storage: -40..+70°C Operating in non-rowed installation: 0..+60°C Operating in rowed installation 0..+50°C
Permissible relative humidity:	5..95% RH (non-condensing)
Scope of delivery:	Interface, USB <> 20 mA industry USB cable with ferrite bead Product CD with driver and manual in German and English





Accessories

*Net unit price for commercial users

Power supplies

Mini USB Power Supply 5V / 1A with Euro plug	11046	16.00€	
Power cable USB A - coax power plug (5.5/2.1mm)	11391	5.00€	

Cable and Connector Accessories

DB9F connection cable with open cable ends, right angled, 1.5m	11903	16.80€	
9-pol. SUB D socket with soldering terminals and shielded housing	11904	9.50€	
9-pol. SUB D socket with screwing terminal and shielded housing	11905	20.00€	
USB 2.0 cable, USB A - USB B, with ferrite, 1.8m	11332	9.50€	

Further accessories

USB-Hub Industry	33601	208.00€	
------------------	-------	---------	---

Mechanical Accessories

Wall mount housing, enclosure rating IP66 / IP67	11120	52.00€	
Mounting bracket for wall mounting	58812	10.50€	
19" DIN rail	58813	19.98€	

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)