

Data sheet:

USB <> RS232 interface Industry



Article no.: 38201

This article has been replaced by the [successor model 38211](#).

Contact

Manual

Drivers

PC controls measuring instrument with RS232 interface via USB

Properties

General information

- Industry-compliant design on account of
 - noise immunity in accordance with EN 61000-6-2
 - Galvanic isolation with an insulation voltage of min. 1 kV
 - Broad supply voltage range of 12 ... 24 V AC / DC
 - Housing for top-hat-rail installation
- Shipped optionally with or without power supply:
Please order power supplies as separate accessories.
- USB 2.0 Full Speed Device (12 Mbit/s)
- Addressable as virtual COM interface under
Windows 98 / Me / 2000 / XP / Server 2003 / Vista / Server 2008 (x86 and x64)
- Supports Mac OS 8, OS 9 and OS X
- Direct Linux support without additional driver from kernel version 2.4.0
- Support of all RS232 data and handshake lines
 - RxD, TxD, RTS, CTS, DSR, DTR, DCD, RI
- **Conforms to standards** both in office and industrial environments:
 - Increased noise immunity for industrial areas
 - Stricter noise emission for residential and commercial areas

Technical data

USB-UART:	FTDI FT232BM
Baud rate:	300..115200 baud
Data format:	Data bit: 7,8 Stop bit: 1,2 Parity: odd, even, no, mark, space
Signal lines:	RxD, TxD, RTS, CTS, DSR, DTR, DCD, RI
USB connection:	"B"-type plug connector
RS232 adapter:	9-pin SUB-D connector, DTE terminal assignment
Power supply:	12..24V DC/AC
Galvanic isolation:	Isolation voltage min. 1 KV DC between all terminals
Current consumption:	approx. 150 mA at 12 V DC
Supply voltage connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Ambient temperature:	Storage: -40..+70°C Operating in non-rowed installation: 0..+60°C Operating in rowed installation 0..+50°C
Permissible relative humidity:	0..95% RH (non-condensing)
Housing:	Plastic compact housing, 105x75x22mm
Weight:	approx. 100 g

Scope of delivery: 1x interface, USB <> RS232 industry
1x USB cable with ferrite bead
1x product CD with driver and manual



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)