

W&I connects

Interfaces for TCP/IP, Ethernet, RS-232, RS-485, USB, 20mA,
glass and plastic fiber optic cable, http, SNMP, OPC, Modbus TCP, I/O digital, I/O analog, ISA, PCI



Data sheet:

20mA <> POF interface for Siemens S5



Article no.: 41015

Unfortunately, this article is no longer available.

PC/PLC connection via fiber-optic cable

Properties

General information

- Conversion from 20mA to FO cable
- Plug compatible with Siemens S5
- Easier installed than any copper cable, thanks to patented FOC adapter
- The interface is very easy to install:
 - Cut the fiber-optic cable with a sharp knife at right angles.
 - Insert end into the patented adapter of the W&T interface.
 - Plug into control system.
 - That's it!
- 100% protection against interfering radiation
- No setting of the transmission parameters necessary
- **Conforms to standards both in office and industrial environments:**
 - High noise resistance per EN 61000-6-2
 - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3

Background information:

Every electrical device generates electromagnetic waves, be it directly (e.g. mobile phone, radio, TV) or as a "by-product". Most affected are thereby other electronic devices, which can be severely disrupted by such radiation, even if they themselves generate electromagnetic waves. This whole issue is referred to as electromagnetic compatibility. Fiber-optic cables do not transmit or generate electromagnetic waves. They also electrically isolate the connected devices.

Technical data

Baud rate:	110..115,200 baud
Data format:	any format
Transfer distance:	max. 100 m
Signal lines:	RxD+/-, TxD+/- (full duplex)
Power supply:	via S5 interface
20mA adapter:	15-pin SUB-D plug, ready for connection to Siemens S5
Fiber-optic cable adapter:	integrated socket with automatic interlocking of the fiber-optic cable
Ambient temperature:	Storage: -40..+70°C Operation: 0..+50°C
Housing:	SUB-D plug housing, 31x55x15mm
Weight:	approx. 30 g
Scope of delivery:	1 x FOC <> 20mA interface for Siemens S5

We are available to you in person:

Wiesemann & Theis GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)