

Data sheet:

Motherbox 3



Article no.: 50504

EUR 298.00

*Net price for commercial users

Measurement data concentrator for Web-I/Os

Use the Motherbox to archive measuring data from Web-I/Os and Web-Thermographs. Determine an individual logging interval for each measuring point available in the network at the frequency you want the current measuring data to be automatically polled and archived in the box-internal database of the Motherbox.

Properties

Interfaces:

- **Network**

Management and connectivity:

- **Configuration**
 - Startup using WuTility (three clicks and you're done)
 - DHCP
 - Web-based management
- **Store and visualize**
 - Inventorying of Web-I/Os using Web-based WuTility
 - Combine measuring values from different Web-I/Os in measuring data profiles and create application-specific overviews
 - Database with measuring values from any number of Web-I/Os directly in the box
 - Create Web-based visualization and control sites for Web-I/Os via drag-and-drop using the Site Creator.

Here a YouTube video needs to be displayed!

You activate the video function using the following button, whereby you use the provider Google and (at your own risk in terms of data protection ;) share data with it.

To avoid such extra clicks in the future, try
eu-de-bonn@ec.europa.eu (Regional representative of the European Commission in Bonn)
or support-de@google.com.

[View summary as PDF](#)

- **For your application**
 - Web server with HTTPS and PHP support
 - MySQL database and SQLite support
 - Run your own C/C++ programs and PHP script time- event driven or at system start.
 - 750 MB for your application data

Power supply:

- **External**
 - Screw terminal
- **Power over Ethernet (PoE)**
 - Phantom power using data pairs
 - Power over unused wire pairs
- **Buffer capacitors**

- controlled shutdown when disconnecting from the power supply

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!
Your suggestions for improvement and additions

Worth knowing

Processing the measurement values

By cyclically polling the Web-IOs a consolidated measurement database is created in the Motherbox. View recorded measurement data directly in the browser, access your application directly via the SQL interface for migrating the measurement data, or export them automatically via FTP.

Use the Motherbox as a visualization server. Use the integrated Site-Creator with drag-and-drop to create Web-based visualization and control pages for Web-IOs.

The internal web server also allows you to upload from your own web pages, which enables creation of web-based applications. For example you can prepare and display recorded measurement data for a specific application.

Technical data

Connections and displays:

Network:	10/100BaseT Autosensing/Auto-MDIX, RJ45
Galvanic isolation:	RJ45 network connection min. 1500 V
Power supply:	Power over Ethernet (PoE) or 24 ... 48V DC (+/-10%) per screw terminal
Supply connection:	Plug-in screw terminal
Current consumption:	PoE Class 2 (3.84 ... 6.49W) and typ. 90mA @ 24V DC with external supply
Indicators and buttons:	System status using multi-color LED Network speed and data transfer Manual device reset

Hard- and software

Processor and memory:	Marvell 88F6180 Flash: 1 GB (NAND) RAM: 128 MB (DDR2)
Operating system:	BusyBox: v1.31.1 Kernel: v4.4.226
Installed software:	ProFTPD: v1.3.6 NGINX: v1.16.1 Samba: v3.6.25 PHP: v7.2.27 MariaDB: v10.2.29 SQLite: v3.29.0

Housing and other data:

Housing:	Plastic housing with integrated DIN rail mount 105 x 22 x 75mm (L x W x H)
Weight:	approx. 100g
Storage temperature:	-40 ... +70°C
Operating temperature:	0 ... 60°C
permissible relative humidity:	0 ... 95% relative humidity, non-condensing
Scope of delivery:	Motherbox 3 Quick start manual Product CD with WuTility management tool and manual

Accessories

*Net unit price for commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug

11021

19.00€ 

Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	34.00€	
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	29.00€	
Mechanical Accessories			
Mounting bracket for wall mounting	58812	9.98€	
19" DIN rail	58813	19.00€	
Supplementary network products			
Ethernet Switch Industry, 4 Port	55604	198.00€	
Software			
WuTility	00104	free	

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestr. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)