

Data sheet:

pure.box 2



Article no.: 50511

This article has been replaced by the expanded successor model [pure.box 3](#).

Ready-to-use industrial PC on DIN rail

Use the pure.box 2 as the basic hardware for your application. The **pre-configured Linux system** comes ready with everything you need for **network- and web-based applications**. The supported database systems **MySQL and SQLite** permit convenient storage of your application data.

Properties

General information

- Use **web servers** for your own applications and upload Web and PHP pages into the pure.box
- **MySQL database** incl. server interface or **SQLite** usable for your own application data
- Run your own **C/C++** programs and **PHP scripts (Java on request)** time- and event controlled
- **750MB** for your own files
- Thanks to **web-based management** complete configuration using your browser
- Support for **HTTPS** encryption and **your own certificates**
- Combination of **multi-color LED** and **buttons** for system status and device reset
- Energy consumption **<2.0W**
- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

Technical data

Network	10/100BaseT autosensing autocrossing
Connections	1 x network (RJ45) Screw terminals for supply voltage (alternative to PoE)
LEDs / Buttons	System status using multi-color LED Current network speed and data transfer Manual device reset
Supply Voltage	Power-over-Ethernet (PoE) 24 ... 48V DC (+ / -10%) using screw terminals
Current draw	60mA @ 24V 40mA @ 48V
Temperatures / Relative humidity	Row mounting: 0 ... 65°C Non-row mounting: 0 ... 70°C 0 ... 90% RH, non-condensing
Housing / Weight	Plastic compact housing (105 x 75 x 22mm) Integrated DIN rail mount approx. 140g
Processor / Memory	Marvell 88F6180 NAND Flash: 1 GB DDR2: 128MB
Operating system	BusyBox: v1.23.2

Installed software GNU/Linux, Kernel: v3.14.43
FTP server: vsftpd v3.0.2
Web server: lighttpd v1.4.35
SMB server: Samba v3.6.25
PHP interpreter: v5.5.25
MariaDB: v5.5.42
SQLite: v3.8.5

Scope of delivery pure.box 2
Quick start manual
W&T Product CD



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)