

Data sheet:

## Microwall Gigabit



Article no.: 55210

**EUR 398.00**

\*Net price for commercial users









### Secure islands (separate yet connected)

The Microwall routes your device islands securely and easily into the corporate intranet. Simple and intuitive selectable filter rules protect sensitive island communication from damaging events in the intranet as well as guarding against undesired access.

## Properties

### Interfaces:

- **2x Ethernet 100/1000BaseT**
  - Autosensing/Auto-MDIX

### Management and connectivity:

- **Remote configuration**
  - Simple startup using WuTility
  - Secure Web-based management using HTTPS only
- **Mode: Standard router**
  - Integration into the routing concept of the intranet
- **Mode: NAT router**
  - Integration of the islands via a single Intranet IP
- **Whitelist-based firewall**
  - Filter rules based on IPv4 addresses and TCP/UDP port numbers
- **Logging**
  - Identification of undesired communication attempts
- **Increased data throughput**
  - Network connection via Gigabit-Ethernet
  - High-performance hardware platform for less latencies

### Power supply:

- **External power**
  - Screw terminals, 24V-48V DC
- **Power-over-Ethernet (PoE)**
  - Phantom power using data pairs
  - Power over unused wire pairs

### Standards & more

- **Conforms to standards both in office and industrial environments:**
  - High noise resistance for industrial environments
  - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!  
[Your suggestions for improvement and additions](#)

## Run modes

The Microwall moves sensitive components or sub-networks into a separate island network and in that way separates it from the

higher level corporate intranet. Connections over the Microwall must be given an express release using rules based on source/destination IP and the needed TCP/UDP port numbers. Communication with documented and/or undesired services is prevented and damaging events such as overload are kept away from the island.

## NAT router mode

Similar to a traditional DSL internet connection, the entire island network is incorporated into the network there via an IP address for the intranet page. No access into the routing concept of the intranet is required. Operating multiple island networks with the same IP areas is also possible in this mode. Machine and systems builders are therefore able to run internal networks with a uniform series IP configuration - no cumbersome modifications to the customer infrastructure.

## Standard router mode

The Microwall acts as a traditional router and the island network is made known in the intranet for example in the form of static routes.

## Filter rules

Microwall rules are simply and clearly managed using Web Based Management and are fully Whitelist based. This means any communication which is not expressly enabled in the form of a rule is blocked.

---

## Technical data

### Connections and displays:

Network:	2x 100/1000BaseT Autosensing/Auto-MDIX RJ45 IPv6 on request
Galvanic isolation:	Network connections min. 1500 V
Power supply:	Power-over-Ethernet (PoE) or DC 24V .. 48V (+/-10%) and AC 18Veff .. 30Veff (+/-10%)
Supply connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Current consumption:	PoE Class 2 (3.84 W to 6.49 W) or for external supply: typ. 150mA @24V DC max. 200mA @24VDC
Indicators:	2x LEDs for network status 1x LED for Error

### Housing and other data:

Enclosure:	Plastic compact housing for top-hat rail mount 105x22x75mm (LxWxH)
Enclosure rating:	IP20
Weight:	approx. 120g
Ambient temperature:	Storage: -40..+85°C Operating 0..+50°C (no stack mounting)
Permissible relative humidity:	5..95% RH, non-condensing
Scope of delivery:	1x Microwall Gigabit 1x Quick Guide

---

## Accessories

\*Net unit price for  
commercial users

### Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	19.00€	
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	34.00€	
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	29.00€	

### Mechanical Accessories

Wall mount housing, enclosure rating IP66 / IP67	11120	49.00€	
Mounting bracket for wall mounting	58812	9.98€	
19" DIN rail	58813	19.00€	

### Supplementary network products

Ethernet Switch Industry, 4 Port	55604	198.00€	
----------------------------------	-------	---------	---

### Software

\* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis  
GmbH  
Porschestra. 12  
42279 Wuppertal  
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5  
p.m.)  
Fax: +49 202/2680-265  
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)