

Data sheet:

## Microwall Gigabit



Article no.: 55210

This article has been replaced by the successor model **Microwall VPN, #55211**.

|              |  |
|--------------|--|
| Contact      |  |
| Firmware     |  |
| Tools        |  |
| Manual       |  |
| Applications |  |

Secure islands (separate yet connected)

The Microwall routes your device islands securely and easily into the corporate intranet. Simple and intuitive selectable filter rules protect sensitive island communication from damaging events in the intranet as well as guarding against undesired access.

## Properties

### Interfaces:

- **2x Ethernet 100/1000BaseT**
  - Autosensing/Auto-MDIX

### Management and connectivity:

- **Remote configuration**
  - Simply startup via WuTility or DHCP
  - Secure Web-based management using HTTPS only
  - All service/management services can be disabled
- **Mode: Standard router**
  - Integration into the routing concept of the intranet
- **Mode: NAT router**
  - Integration of the islands via a single Intranet IP
- **Whitelist-based firewall**
  - Filter rules based on IPv4 addresses and TCP/UDP port numbers
- **Logging**
  - Identification of undesired communication attempts
- **Increased data throughput**
  - Network connection via Gigabit-Ethernet
  - High-performance hardware platform for less latencies

### Power supply:

- **External power**
  - Screw terminals, 24V-48V DC
- **Power-over-Ethernet (PoE)**
  - Phantom power using data pairs
  - Power over unused wire pairs

### Standards & more

- **Conforms to standards both in office and industrial environments:**
  - High noise resistance for industrial environments
  - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!  
Your suggestions for improvement and additions

---

## Run modes

The Microwall moves sensitive components or sub-networks into a separate island network and in that way separates it from the higher level corporate intranet. Connections over the Microwall must be given an express release using rules based on

source/destination IP and the needed TCP/UDP port numbers. Communication with documented and/or undesired services is prevented and damaging events such as overload are kept away from the island.

## NAT router mode

Similar to a traditional DSL internet connection, the entire island network is incorporated into the network there via an IP address for the intranet page. No access into the routing concept of the intranet is required. Operating multiple island networks with the same IP areas is also possible in this mode. Machine and systems builders are therefore able to run internal networks with a uniform series IP configuration - no cumbersome modifications to the customer infrastructure.

## Standard router mode

The Microwall acts as a traditional router and the island network is made known in the intranet for example in the form of static routes.

## Filter rules

Microwall rules are simply and clearly managed using Web Based Management and are fully Whitelist based. This means any communication which is not expressly enabled in the form of a rule is blocked.

---

## Technical data

### Connections and displays:

|                      |  |
|----------------------|--|
| Network:             | 2x 100/1000BaseT Autosensing/Auto-MDIX<br>RJ45<br>IPv6 on request                                    |
| Galvanic isolation:  | Network connections min. 1500 V  |
| Power supply:        | Power-over-Ethernet (PoE) or<br>DC 24V .. 48V (+/-10%) and<br>AC 18Veff .. 30Veff (+/-10%)           |
| Supply connection:   | Plug-in screw terminal, 5.08mm spacing<br>Labeled "L+" and "M"                                       |
| Current consumption: | PoE Class 2 (3.84 W to 6.49 W)<br>or for external supply:<br>typ. 150mA @24V DC<br>max. 200mA @24VDC |
| Indicators:          | 2x LEDs for network status<br>1x LED for Error   |

### Housing and other data:

|                                |   |
|--------------------------------|---|
| Enclosure:                     | Plastic compact housing for top-hat rail mount<br>105x22x75mm (LxWxH) |
| Enclosure rating:              | IP20  |
| Weight:                        | approx. 120g  |
| Ambient temperature:           | Storage: -40..+85°C<br>Operating 0..+50°C (no stack mounting)         |
| Permissible relative humidity: | 5..95% RH, non-condensing   |
| Scope of delivery:             | 1x Microwall Gigabit<br>1x Quick Guide                                |



### We are available to you in person:

Wiesemann & Theis  
GmbH  
Porschestr. 12  
42279 Wuppertal  
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)  
Fax: +49 202/2680-265  
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)