

Data sheet:

Fix Defined Firewall



Article no.: 55312

EUR 498.00

*Net price for commercial users

[Add to cart](#)[Sample order](#)[Request a quote](#)[Contact](#)[Manual](#)[Applications](#)

Network one-way street

The Fix Defined Firewall links computers to networks with no feedback, so that the computers are able to receive only. All received network packets are passed on in one direction to the reading host. Data traffic to the safe network is not possible - neither from the reading computer nor from the firewall itself.

Properties

Interfaces:

- **2x Ethernet 100BaseT**
 - Autosensing/Auto-MDIX

Power supply:

- **External power**
 - Screw terminals, 24V-48V DC
- **Power-over-Ethernet (PoE)**
 - Phantom power using data pairs
 - Power over unused wire pairs

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!
Your suggestions for improvement and additions

Feedback-free

Feedback-free network connection

The Fix Defined Firewall is a fixed configured firewall for unidirectional data flow. Data packets arriving at the input are passed transparently to the output, with the opposite direction completely blocked. This pre-configuration cannot be changed. The Fix Defined Firewall has no configuration interface, none of its own network services, and no Ethernet address. For applications for example in telemetry or data flow analysis this ensures feedback-free connection of receiving computers to a network with high security requirements.

Due to its clearly defined scope of function the firmware for the Fix Defined Firewall needs no traditional operating system and is free of open source and third-party components.

Startup is true plug and play, and in PoE environments requires only connection of the network cables. Without PoE, the supply voltage is additionally required - that's it.

Technical data

Connections and displays:

Network: 2x 100BaseT Autosensing/Auto-MDIX

	RJ45
Galvanic isolation:	Network connections min. 1500 V
Supply voltage:	Power-over-Ethernet (PoE) or DC 24V .. 48V (+/-10%) and AC 18Veff .. 30Veff (+/-10%)
Supply connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Current consumption:	PoE Class 1 (0.44W - 3.84W) or for external supply: typ. 80mA @24V DC max. 95mA @24VDC
Indicators:	2x LEDs for network status 1x LED system 1x LED power

Housing and other data:

Housing:	Plastic compact housing for top-hat rail mount 105x22x75mm (LxWxH)
Enclosure rating:	IP20
Weight:	approx. 120g
Ambient temperature:	Storage: -40..+85°C Operating 0..+60°C (non-contiguous mounting)
Permissible relative humidity:	5..95% RH, non-condensing
Scope of delivery:	1x Fix Defined Firewall 1x Quick Guide

Accessories

*Net unit price for
commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	19.00€	
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	34.00€	
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	29.00€	

Mechanical Accessories

Mounting bracket for wall mounting	58812	9.98€	
19" DIN rail	58813	19.00€	
Wall mount housing, enclosure rating IP66 / IP67	11120	49.00€	

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)