

Product overview:

Measuring technology accessories

Article no.	Description	Design
57011	Temperature sensors for indoor use Pt-100 cable sensor Class A Cable length 2m Enclosure rating: IP67 4-wire connection Pigtail cable Temperature range -50°C180°C Maximum measuring error: ±0.15°C, ±0.2%	
57014	Temperature sensors for outdoor use Pt-100 cable sensor Class B 4-wire connection IP65 housing for outdoor use Temperature range -50°C90°C Maximum measuring error: ±0.3°C, ±0.5%	
57021	Water spray protection for Thermo-Hygro-Baro Sensor Retrofitting the sensor with sintered bronze cap IP X4 protection Sealing rating per DIN 40050: 1993 Part 9	

Article list

*Net unit price for commercial users

Pt-100 cable sensor, Class A, IP67 with 2m cable, 4-wire with open cable ends

57011

22.00€

Pt-100 external probe, class B, 4-wire, IP65 housing

(This outdoor sensor cannot be calibrated)

Retrofit with sintered cap for 57713/57720/57613/57620

57021

22.00€

□

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis GmbH

Porschestr. 12 42279 Wuppertal

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)

Fax: +49 202/2680-265

info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.