







Data sheet:

Web-IO 1x Thermometer



Article no.: 57601

This article has been replaced by the expanded successor model [Web Thermometer, NTC #57714](#).

Contact	
Manual	
Tools	
Firmware	
Applications	
FAQs	

Temperature monitoring via SNMP, TCP/IP-Socket, UDP, Web-Browser ...

Properties

- **Monitor temperatures and processes through a browser**
 - HTML page design user-variable
 - Direct access to current temperature value, e.g., for integration into other Web pages
- **SNMP temperature polling /Alarm traps** for incorporating into your existing SNMP management system
- **E-mail for alarm or reporting functions**
- **Connections:**
 - 10/100MBit
 - NTC probe included, PT100 probe can be connected
- **Easy Start:**
 - Connect sensor and network cable
 - Connect supply voltage
 - Assign IP number
 - That's it!

Technical data

Temperature sensor:	NTC and PT100 connection
Network:	10/100BaseT autosensing
Supply voltage:	12-24V AC / DC using screw terminal
Measuring unit	
Sensor:	NTC 10k, PT100-connection, 2-,3- or 4-wire
Measuring range:	-45°C...75°C
Resolution:	1/10°C
Measuring error:	±0.3°C, ±5% (NTC) ±0.3°C, ±2% (PT100)
Polling frequency:	1, 5, 15, 60 min
Memory depth (64k):	min. 6 weeks, max. 390 weeks
Deviation of the internal clock:	max. 4.32 min. / month
Other data	
Galvanic isolation:	Measurement inputs to network: min. 500V
E-mail function:	Mail for sending alarms or as reporting function
Supply voltage:	DC 12V (-5%) - 34V (+5%) AC 9Veff (-5%) - 24Veff (+5%) DC 48V (+10%) on request
Current draw:	AVG: 170mA @ 12VDC, 80mA @ 24VDC
Power supply:	Supplied power adapter or 12..24 V DC/AC
Configuration interface:	Serial port RS232, 9600 baud, 8 data bits, 1 stop bit, no parity
Enclosure:	Plastic compact enclosure, 105x75x22mm
Weight:	approx. 200g
Ambient storage temperature:	-40..+70°C

Ambient operating temperature: 0 .. +60°C

Scope of delivery: 1x Web Thermometer for top-hat rail mount
1x NTC thermocouple
1x AC adapter



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)