

Data sheet:

Web-Thermograph 8x



Article no.: 57608

This article has been replaced by the expanded successor model [Web Thermometer 8x](#).

Contact
Product overview
Manual
Tools
Firmware
Applications
FAQs

Measure, log and report...

The Web-Thermograph 8x is an instrument that measures [eight temperature values](#) and makes the values available in the network. The device includes an integrated data logger and numerous Web and network services for manual querying of the measurements or provides autonomous sending of messages.

Properties

Sensor:

- **Eight temperature inputs Pt100/Pt1000**
 - Measuring range of W&T probe: -50°C...180°C
 - Measuring input: -200°C...650°C

Connectivity:

- **Monitor temperatures and curves with your browser**
- **Alarm and reporting function:**
 - E-mail for alarm or reporting functions
 - SNMP polling / alarm traps
 - Up to 8 alarm messages can be configured
- **Dynamic integration into other Web sites:**
 - Direct access to current measurement values via AJAX, JavaScript and Java applet
- **Additional software interfaces for incorporating into your systems/databases:**
 - OPC server
 - Syslog
 - Sensobase (database integration via ODBC)
 - TCP and UDP sockets, client and server
 - FTP (data logging)
- **Possible applications:**
 - Monitor temperatures in the server room, network cabinet or office
 - Direct display of multiple measuring points in the browser via Java applet
 - Logging of measurements via FTP, Excel file, email attachment and internal memory
 - Green IT: Monitor efficiency of the server room climate control

Data logger:

- **Internal data logger**
 - Memory size: min. 4 weeks, max. 4 years
 - Save frequency: 1, 5, 15, 60 min
- **Document measurement data online in the [W&T Cloud](#) and access from anywhere in the world**
- **Internal clock**
 - Time synchronization via time server calibration
 - Battery-backed device clock

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

Technical data


Connections and displays:

Temperature sensor:	8x PT100/Pt1000 inputs via screw terminal Cable length for W&T probe: 2m (can be extended as needed)
Network:	10/100BaseT autosensing IPv6 on request
Galvanic isolation:	Measurement inputs to network: min. 500V
Supply voltage:	DC 12V (-5%) - 34V (+5%) AC 9Veff (-5%) - 24Veff (+5%) DC 48V (+10%) on request
Current consumption:	typ. 200mA @12VDC, 100mA @24VDC, 100mA @20VAC max. 240mA @12VDC
Displays:	1 LED Power 4 LEDs Status and Error


Measuring unit:

Sensor:	8x PT1000, and PT100 connection, 2-,3- or 4-conductor
Measuring range:	W&T sensor: -50°C...180°C PT100/PT1000 measuring input: -200°C...650°C
Resolution:	1/10°C
Maximum measuring error:	

Measuring unit $\pm 0,26^{\circ}\text{C}$, $\pm 0,3\%$



PT100/1000 Sensor Class A $\pm 0.15^{\circ}\text{C}$, $\pm 0.2\%$



Measuring frequency:	Measurement every 4 sec. / 15 measurements per min.
Storage frequency:	1, 5, 15, 60 min
Memory depth (832k):	min. 4 weeks, max. 4 years
Deviation of the internal clock:	max. 1 min. / month

Housing and other data:

Housing:	Compact plastic housing, 106.8mm x 87.8mm x 62.6mm (l x w x h)
Enclosure rating:	IP20
Weight:	approx. 200g
Ambient storage temperature:	-40...+70°C
Ambient operating temperature:	0 ... +60°C
Scope of delivery:	1x Web-Thermograph 8x for DIN rail mount 1x PT100 sensor

Please order power supplies separately as accessories



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)