

Data sheet:

Web-IO Analog-In 2x 0..10V



Article no.: 57643

This article has been replaced by the expanded successor model [Web-IO Analog-In/Out 2x 0-10V](#).

- Contact 
- Applications 
- Tools 
- FAQs 
- Manual 
- Firmware 

Gather, monitor and archive analog measurement values over the Internet/Intranet

Properties

General information

- **Monitor measured values and trends from a browser**
 - HTML page design user-variable
 - Direct access to the actual value, e.g., for integration into other Web pages
- **Graphic display of the stored temperature values**
 - Chart display
 - Interactive display, user-scalable
 - Display of limit violations
 - Freely selectable line color
- **E-mail for alarm or reporting functions**
- **SNMP measurement queries / alarm traps** for incorporating into your existing SNMP management system
- **Querying measured data with OPC**
- **Sensing alarms via syslog, TCP, SNMP, e-mail**
- **Archiving via FTP and W&T database tool [Sensobase®](#)**
- **Time synchronization using time server calibration**
- **Adapters:**
 - 10/100MBit
 - 2x 0..10V voltage input
- **Easy Start:**
 - Connect measurement lines and network cable
 - Connect supply voltage
 - Assign IP number
 - That's it!
- **Software interfaces**
 - HTTP, Web browser
 - AJAX, JavaScript and Java applet
 - TCP and UDP sockets, client and server
 - OPC server
 - SMTP (e-mail)
 - SNMP (including trap)
 - SYSLOG
 - FTP (data logging)
- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

Technical data

Voltage input: 2x 0..10V, 1MΩ
 Network: 10 / 100BaseT autosensing
 IPv6 on request

Measuring unit

Resolution 2x voltage input: 1.25mV
Measuring error: max. 0.5% FSR (Full Scale Range 0..10V) $T_A = 0-60^{\circ}\text{C}$

Storage frequency: 1, 5, 15, 60 min
Memory depth (832k): min. 79 days, max. 17 years
Deviation of the internal clock: max. 4.32 min. / month (without time server calibration)
max. 3 sec. (with time server calibration)
Measurement value acquisition (can be polled over the network and can generate alarms if desired): 2/second
Saving in the internal data logger 1/Minute

Other data

Galvanic isolation: Measurement inputs to network: min. 500 volts
E-mail function: Mail for sending alarms or as reporting function
Supply voltage (uses screw terminals): DC 12V .. 48V (+/-10%)
AC 12Veff .. 30Veff (+/-10%)
Current consumption: AVG: 185mA @12VDC, 90mA @24VDC
Housing: Plastic compact housing, 105x75x22mm
Weight: approx. 200g
Ambient storage temperature: -40 .. +70°C
Ambient operating temperature: 0 .. +60°C
Scope of delivery: 1x Web-IO Analog-In 2x 0..10V
for DIN rail mount
1x product CD with
WuTility management tool, OPC server,
programming examples for VB/Delphi, SNMP-MIB,
reference manual in German/English

Please order power supplies separately as accessories



[We are available to you in person:](#)

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)