

Data sheet:

Web-IO 4.0 Analog 0-20mA



Article no.: 57761

EUR 338.00

*Net price for commercial users

[Add to cart](#)
[Sample order](#)
[Request a quote](#)
[Contact](#)
[Firmware](#)
[Manual](#)
[FAQs](#)
[Tools](#)
[Applications](#)

Measure, tunnel, output analog signals...

The combined solution for analog **in-** or **output signals** brings your measurements into the network and back to the terminal. Use the Web-IO Analog-In/Out to measure **analog signals**, tunnel them over the network and output them again as analog signals at a remote location.

Properties

Analog connection:

- Two channels, selectably configurable as:
 - **Current input:**
 - Input signal: 0/4..20mA active/passive
 - **Current output:**
 - Output signal: 0/4..20mA

Connectivity:

- **Intuitive Web interface** for simpler configuration
- **Monitor analog measurements and processes from a browser**
- **Alarm and reporting function:**
 - E-mail for alarm or reporting functions
 - SNMP polling / alarm traps
 - Configure up to 12 alarm messages
- **Box2Box mode** tunnels analog signals between two devices
- **Set analog values via socket command or direct entry**
- **Active current input** 0/4-20mA
- **Interactive display**, custom scalable
- **Dynamic integration into other Web sites:**
 - Direct access to current measurement values, e.g. JavaScript (AJAX).
- **Current Industry 4.0 protocols:**
 - OPC UA, REST and **MQTT** support
- **Additional software interfaces for incorporating into your systems/databases:**
 - SNMPv1, SNMPv2c, SNMPv3
 - OPC UA, OPC DA
 - Syslog
 - Sensobase (database integration via ODBC)
 - TCP and UDP sockets, client and server
 - FTP (data logging)
 - Modbus TCP
- **Possible applications:**
 - Connect each sensor with 0/4..20mA output and monitor measurements
 - Control analog actuators over the network
 - Network as extension: tunnel analog values via Box2Box mode
 - Direct display of multiple measuring points in the browser via Java applet
 - Logging of measurements via FTP, Excel file, email attachment and internal memory

Data logger:

- **Internal data logger**
 - Memory capacity: min. 150 days, max. 99 years
 - Save frequency: 15, 30 sec, 1, 5, 15, 60 min
- **Document measurement data online in the [W&T Cloud](#) and access from anywhere in the world**
- **Internal clock**
 - Time synchronization via time server calibration
 - Battery-backed device clock

Standards & more

- **Supply voltage via Power-over-Ethernet (PoE)**
 - Phantom power using data pairs
 - Power over unused wire pairs
 - External power supply is an alternative
- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!
Your suggestions for improvement and additions

Technical data

Connections and displays:

Current input passive:	0/4..20mA, 100Ohm
Current input active:	0/4..20mA, burden max. 500 Ohms, active voltage U_{max} 14V / 40mA
Current output:	0/4..20mA, burden max. 500 Ohms, supply 10V guaranteed
Analog in-/output:	8-pin terminal block Conductor cross-section 0.2-1.3mm ² Stripped length 6-8mm
Current loop monitoring:	Short circuit protected and open-loop detection
Network:	10/100BaseT autosensing RJ45 IPv6 on request
Galvanic isolation:	Measurement inputs to network: min. 1500 volts
Power supply:	Power-over-Ethernet (PoE) or DC 12V .. 48V (+/-10%)
Current consumption:	PoE Class 1 (0.44 - 3.84W) typ. 100mA @ 24V DC with external supply
Displays:	1 LED power 2 LEDs network status 4 LEDs status and error

Measuring unit:

Resolution:	Current input: 2.5μA
Measuring error:	max. 0.5% FSR (Full Scale Range 0..20mA) $T_A = 0-60^{\circ}C$
Storage frequency:	15, 30 sec., 1, 5, 15, 60 min
Storage depth:	min. 150 days, max. 99 years
Measurement value acquisition (can be polled over the network and can generate alarms if desired):	2 / second

Housing and other data:

Housing:	Plastic compact housing for top-hat rail mount 105x22x75mm (LxWxH)
Enclosure rating:	IP20
Weight:	approx. 140 g
Ambient storage temperature:	-40..+70°C
Ambient operating temperature:	0 .. +60°C
Scope of delivery:	1x Web-IO Analog-In/Out 2x 0..20mA PoE for DIN rail mount 1x Quick Guide in German/English

Accessories

*Net unit price for commercial users










Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug

11021

21.00€



Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00€	
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	33.00€	
Storage and Visualization			
Motherbox 3	50504	328.00€	
Mechanical Accessories			
Mounting bracket for wall mounting	58812	11.20€	
19" DIN rail	58813	21.00€	
Supplementary network products			
Ethernet Switch Industry, 4 Port	55604	218.00€	
Free Product CD			
W&T Product CD (manual, tools & drivers)	10001	optional	
Software			
WuTility	00104	free	
OPC Server	00103	free	
Sensobase®	00107	free	

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)