

Data sheet:


Web-IO 4.0 230V Relay 4xNO, 4xCO



Article no.: 57838

EUR 298.00

*Net price for commercial users

Add to cart Sample order Request a quote Contact Applications Firmware Tools Manual 

Switch remotely...

Using the Web-IO 4.0 230V Relay 4xNO, 4xCO you can control [230V switching signals](#) via TCP/IP Ethernet. There are numerous Web and network services available for switching up to 6A with the eight integrated relays - even directly from the browser or from a smart phone. Using protocols such as [MQTT](#) and [REST](#) the Web-IO is an ideal fit in the world of Industry 4.0 and the Internet of Things.

Properties

Switching signals:

- **8 switching outputs:**
 - 4 x potential-free normally open contacts for 230V mains
 - 4 x potential-free changeover contacts for 230V mains
 - Switching currents up to max. 6A

Connectivity:

- **Intuitive Web interface** for simpler operation
 - Select between German or English
 - Switching the outputs directly from the Web interface
 - Adaptation for smartphone
 - HTTP and HTTPS
- **Current Industry 4.0 protocols:**
 - REST and [MQTT](#) support
 - AMQP on request
- **Box-to-Box**
 - Pass switching signals over the network 1:1
- **Alarm and reporting functions:**
 - Email for alarm sending or as status report
 - SNMP polling / alarm traps
 - Switching your outputs in alarm situations
 - Switching the outputs on another Web-IO
 - HTTP requests for controlling third-party devices
 - Up to 12 actions can be configured
- **Dynamic integration into other Web sites:**
 - Direct access to the contacts via HTTP requests, AJAX and JavaScript
- **Additional software interfaces for incorporating into your systems/databases:**
 - OPC
 - Modbus TCP
 - Syslog
 - TCP and UDP sockets, client and server
 - FTP (data logging)
- **Internal clock**
 - Time synchronization via time server calibration
 - Battery-backed device clock
- **Possible applications:**
 - Cross-location switching
 - House and building automation
 - Light, gate and cabinet control
 - More uses can be found [here](#).

Power supply:

- **External power**
 - Screw terminal

- 230V AC (50Hz)

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!
Your suggestions for improvement and additions

Technical data

Connections, displays and control elements:

Digital switching outputs: 4 x potential-free normally open contacts, max. 6A
4 x potential-free changeover contacts, max. 6A
Network: 10/100BaseT autosensing
Power supply: 230V AC (approx. 15mA@230V)
Galvanic isolation: Digital output to network: min. 1000 V
Adapters: 1 x 3x screw terminals for power
2 x 11x screw terminals for the outputs
1 x RJ45 for network
Indicators: Status LEDs for network
2 LEDs for switching states

Data transmission:

Protocols: HTTP and HTTPS
TCP and UDP sockets, client and server
MQTT - Publish and Subscribe
REST
SNMP including traps
SMTP e-mail sending
OPC server
Modbus TCP
Inventory keeping, group management
Response times: Data and switching traffic: typically 12 ms

Housing and other data:

Housing: Plastic housing for top hat rail installation
90x116x56 mm (LxWxH)
Enclosure rating: IP20
Weight: approx. 330 g
Storage temperature: -25°C - 70°C
Operating temperature: 0°C - 60°C
Permissible relative humidity: 5..95% RH (non-condensing)
Scope of delivery: 1 x Web-IO 4.0 230V Relay 4xNO, 4xCO
1 x Quick Guide
Power supply and other accessories can be ordered separately

Accessories

*Net unit price for commercial users

Mechanical Accessories

19" DIN rail	58813	19.00€	
Wall mount housing, enclosure rating IP66 / IP67	11120	49.00€	


Supplementary network products

Ethernet Switch Industry, 4 Port	55604	198.00€	
----------------------------------	-------	---------	---

Free Product CD

W&T Product CD (manual, tools & drivers)	10001	optional	
---	-------	----------	--

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)