



Data sheet:

## RS422 > Centronics interface, 1+1 Kbytes



Article no.: 62009

**EUR 168.00**
\*Net price for  
commercial usersAdd to cart Sample order Request a quote Contact Manual 

Use Centronics printers on differential interfaces

The model 62009 Interface connects parallel printers or plotters to industrial RS422 data sources and makes expensive special printers unnecessary.

## Properties

### Interfaces:

- **1 x RS422**
  - 25-pin SUB-D socket
- **1 x Centronics**
  - 36-pin plug integrated in interface housing

### Management and connectivity:

- **Convenient startup**
  - Automatic detection of the RS232 parameters
- **Interface for all purposes**
  - Baud rates between 300 and 76,800 baud
  - Electronic system discretely secured in the adapter housing of the printer cable
  - Large safety fifo for slow handshake procedures
  - Integrated print data buffer

### Power supply:

- **External**
  - via supplied AC adapter (only with Euro plug)

### Standards & more

- **Conforms to standards both in office and industrial environments:**
  - High noise resistance for industrial environments
  - Low noise emission for residential and business areas
- **5 year guarantee**

♥ Wish for something!  
Your suggestions for improvement and additions

## Technical data

### Connections and displays:

Serial port:	RS422 Interface 25-pin SUB-D socket incl. 2m connection cable on device
Parallel port:	36-pin Centronics plug, interface Can be plugged directly to the printer
Baud rate:	300 .. 76,800 baud
Data format:	7, 8 data bits, No, Even, Odd Parity
Handshake:	DTR, XON/XOFF handshake
Buffer:	2kB (1 kB + 1 kB overflow buffer)
Power supply:	Supplied power adapter

Current consumption: approx. 50mA

#### Housing and other data:

Enclosure: Plastic housing, 75 x 61 x 20mm (L x W x H)  
Enclosure rating: IP20  
Weight: 425g incl. power adapter  
Scope of delivery: RS422 > Centronics interface  
AC adapter for office use (only with Euro plug)

---

\* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



#### We are available to you in person:

Wiesemann & Theis  
GmbH  
Porschestra. 12  
42279 Wuppertal  
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5  
p.m.)  
Fax: +49 202/2680-265  
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)