

Data sheet:

RS232 line driver set Industry



Article no.: 80201

EUR 248.00

*Net price for commercial users

Add to cart

Sample order

Request a quote

Contact

Manual

Reliably transmit serial data over long distances

The Line Driver Set 80201 connects RS232 devices over a distance of up to 1200 meters with galvanic isolation.

Properties

Interfaces:

- **1 x RS232 per converter**
 - 9-pin Sub-D plug with PC pin assignments
- **1 x RS422 per converter**
 - 9-pin Sub-D plug
- **Galvanic isolation between the ports**
 - Isolation voltage 1kV DC

Management and connectivity:

- **Transmission speed up to 115,200 baud**
- **No re-configuration of transmission parameters required**

Voltage supply:

- **External**
 - 12V-24V AC/DC
 - Galvanically isolated power connection
- **Integrated overvoltage protection**

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance for industrial environments
 - Low noise emission for residential and business areas
- **5 year guarantee**

Wish for something!
Your suggestions for improvement and additions

Worth knowing

When transmitting data over long distances it is virtually impossible to prevent potential differences between the connected devices. These can be caused by remote lightning strikes, but even in normal operation can arise from switching operations of high-power electrical consumers. In case of a potential shift the data line is misused for compensating the voltage difference. Potential differences of only 7V can already result in faulty transmission, whereas differences of more than 30V could destroy interface components. For this reason use of a potential isolator for connections over long distances is one measure which drastically increases the life expectancy of the connected devices.

Technical data

Connections and displays:

Serial Port A: RS232 Interface
9-pin SUB-D adapter, PC assignment

Serial Port B: RS422 Interface
9-pin SUB-D adapter

Baud rate: 0..115,200 baud

Data format: any format

Galvanic isolation: Isolation voltage min. 1 KV DC between all terminals

Max. distance: 1200m

Supported signals: 2 data and 2 handshake signals

Supply voltage: 12..24V AC/DC

Current consumption: typ. 80mA @12V DC, 40mA @24V DC

Displays: 1 LED Power
1 LED Data

Housing and other data:

Housing: Plastic compact housing for top hat rail installation
105 x 22 x 75mm (L x W x H)

Enclosure rating: IP20

Weight: approx. 200g

Ambient temperature: Storage: -40..+70°C
Operation: 0..+60°C

Permissible relative humidity: 5..95% RH (non-condensing)

MTBF: 328,240h @25°C per MIL-HDBK-217

Life expectancy: > 25 years at 25°C ambient temperature

Scope of delivery: RS232 line driver set Industry
Please order power supplies separately as accessories



Accessories

*Net unit price for commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	21.00€	
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00€	
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	33.00€	

Cable and Connector Accessories

RS232 PC/PC cable, DB9F x DB9F, 1.8m	11992	9.90€	
9-pol. SUB D socket with screwing terminal and shielded housing	11905	21.00€	

Mechanical Accessories

Wall mount housing, enclosure rating IP66 / IP67	11120	54.00€	
Mounting bracket for wall mounting	58812	11.20€	
19" DIN rail	58813	21.00€	

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis
GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)