

Data sheet:

Interface - plastic fiber optic <> RS232 Industry, with handshake



Article no.: 81202

Unfortunately, this article is no longer available.

Contact

Manual

PC connection over fiber-optic cables with handshake

Properties

General information:

- Sending of the data lines RxD and TxD and the handshake lines RTS and CTS
- No setting of the transmission parameters necessary
- External supply also makes it suitable for low-power RS232 interfaces
- Wide supply voltage range 12..24V AC/DC
- Housing suitable for installation on top hat rails

Background information:

RS232 interfaces do not always supply the power necessary for smart solutions with supply voltage-free fiber-optic interfaces. Especially as regards the notebook interfaces, energy saving measures to extend the operating time can lead to a situation where the maximum fiber-optic transmission distance of 100 m is not always available. For such cases, the FOC <> RS232 interface, Industry, offers a solution by providing a separate power supply.

Technical data

Baud rate:	0..57600 kBaud
Data format:	any format
Signal lines:	RxD, TxD, RTS, CTS
RS232 adapter:	9-pin SUB-D adapter
Fiber-optic cable adapter:	Integrated socket with automatic interlocking of the fiber-optic cable
Fiber-optic medium:	Duplex plastic optical fiber cable Dimensions 2.2 x 4.4 mm with a fiber diameter of 1 mm Material: core: PMMA, cladding: PE
Transfer distance:	maximum 50 meters fiber optic cable
Galvanic isolation:	Isolation voltage min. 1 KV DC between supply and serial connection
Power supply:	12..24V DC/AC
Current consumption:	approx. 80 mA at 12 V input voltage
Supply voltage connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Ambient temperature:	Storage: -40..+70°C, Operation: 0..+50°C
Permissible relative humidity:	5..95% RH (non-condensing)
Housing:	Plastic compact housing, 105x75x22mm
Weight:	approx. 100 g
Scope of delivery:	1x FOC <> RS232 interface, Industry



[We are available to you in person:](#)

Wiesemann & Theis
GmbH
Porschestr. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)