

Data sheet:

## RS232 2 Computer Adapter



Article no.: 85211

This article has been replaced by the successor model [RS232 Multi Computer Adapter 85603](#).



2 PCs share one serial printer/plotter

### Properties

#### General information:

- 2 PCs share one serial printer/plotter
- Automatic switching on "first come, first served" basis
- Baud rates and protocol conversion
  - Individual configuration of interfaces
  - Fully automatic operation
- Data return channel allow for connection of bi-directional peripherals

### Technical data

Baud rate:	50..76,800 baud
Data throughput:	max. 38400 Bis/s total from incoming and outgoing channel
Data format:	7,8 data bits, no,even,odd parity
Flow control:	Hardware handshake or XON/XOFF protocol
Switching:	time-controlled, switching time 5 seconds per EPROM patch, adjustable within wide limits
Code conversion:	Individual code conversion per EPROM patch in both directions
Power supply:	Supplied power adapter
Current consumption:	approx. 100 mA
Inputs:	25 pin SUB-D sockets including 0.5 m cable, DTE assignment
Output:	25-pin SUB-D adapter including 2m cable, DCE assignment
Housing:	Plastic housing, 124x74x21 mm
Weight:	approx. 500g incl. power adapter
Scope of delivery:	1 x RS232 2 computer adapter 1x power adapter for application in office

© Wieseemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)