

Data sheet:

RS232 Portable Buffer, 128KB



Article no.: 88127

This article has been replaced by the successor model [RS232 Portable Buffer 88241](#).

Storage and transfer of machine data

Properties

General information:

- Portable memory for
 - measuring data
 - machine data
 - demo texts
- Control by means of keys or control sequences
- Suitable as demobox for single or cyclic data output

Background information:

Sometimes, it is not possible to lay a cable between the computer and printers or other devices. However, the transfer of data on disks is often not practical (due to incompatibility or the lack of a floppy drive at the devices), or simply too cumbersome and risky (viruses). Printouts of logs are normally only required in the event of a disruption. Why should such data therefore be printed constantly? In these situations, portable buffers are the ideal solution. They are connected to the computer instead of a printer, and all print data is read into the buffer.

Technical data

Capacity:	32 KB, 128 KB or 512 KB
Baud rate:	150..19,200 baud
Data format:	7,8 data bits, no,even,odd parity
Flow control:	Hardware handshake or XON/XOFF protocol
Output modes:	Single or cyclic
Power supply:	4.8V NiCd battery, 225 mAh Supplied power adapter
Recharging time:	24 hours
Data storage time:	approx. 14 days
Input/output:	9-pin SUB-D adapter integrated into buffer housing, PC assignment
Operating elements:	Record and replay key
Housing:	Plastic housing, 124x74x21 mm
Weight:	approx. 400g incl. power adapter
Scope of delivery:	1x RS232 portable buffer 1x power adapter for application in office

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5
p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wieseemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes,
none of our statements should be applied without verification. Please let us know of any errors
or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)